



型号Model: SLC2-HT  
 量程Capacity: 30t  
 精度Accuracy Class: C2  
 灵敏度Sensitivity: 2.0mV/V ±0.2%  
 安全过载Safe overload: 150%  
 极限过载Ultimate overload: 300%

防护等级Protection: IP67  
 激励电压Excitation range: 5~18V (DC)  
 温度范围Temperature range: -40~+70 °C

电缆长度Cable length: 6m  
 电源Excitation+: 红 red  
 电源Excitation-: 黑 black  
 信号Signal+: 绿 green  
 信号Signal-: 白 white  
 屏蔽Shield: 黄 yellow

输入阻抗Input resistance: 775±5 Ohms  
 输出阻抗Output resistance: 702±2 Ohms

图纸中未注明的要求按以下: 表面粗糙度: 3.2 未注尺寸公差: ±0.30 (MAX) 未注圆角: R0.5 未注倒角: 0.5*45°		完成或总结:		锐边倒钝 去毛刺处理 表面不得划痕		<b>Maken</b> Maken Electric 宁波马加机电有限公司 主题, 系列: XXX-XX 系列	
制图	Bowey	姓名	签字	日期	备注	产品/物料编码/备注:	
审核							
批准							
This document must not be copied without the written permission of NingboMaken. The contents thereof must not be disclosed to a third party nor be used for any unauthorized purpose. 未经宁波马加机电有限公司授权/许可不得使用本图纸的任何部分				材料/Material:		零件名称: SLC2-HT-传感器_30t	
www.makenie.com		www.loadcell.cn		净重N/W:	9	比例: 1:2	A3 SHEET 1 OF 1